

## COATING COMPOSITION, ITS PRODUCTION METHOD, CURED ITEM, AND COATING FILM

**Patent number:** JP2002371234  
**Publication date:** 2002-12-26  
**Inventor:** KANAMORI TARO; HONDA YOSHIKAZU;  
HASHIGUCHI YUICHI  
**Applicant:** JSR CORP  
**Classification:**  
- international: C09D183/04; B01J35/02; B32B27/00; C09D7/12;  
C09D183/06; C09D183/12  
- european:  
**Application number:** JP20010363541 20011129  
**Priority number(s):**

### Abstract of JP2002371234

**PROBLEM TO BE SOLVED:** To provide a coating composition which is excellent in photocatalyst dispersibility, is excellent in storage stability even in a state of a high concentration, gives a coating film excellent in durability and adhesiveness, and has a photocatalytic function; and its production method.  
**SOLUTION:** This coating composition contains (a) an organosilane which is represented by the formula:  $(R<1>)_n Si(OR<2>)_4-n$  (wherein  $R<1>$  is a 1-8C monovalent organic group;  $R<2>$  is a 1-5C alkyl or acyl group; and  $n$  is 0, 1 or 2) provided the organosilane may be (a-1) a substituted derivative wherein  $n$  is 1 or 2 and  $R<1>$  has at least one epoxy group or may be (a-2) one wherein  $R<1>$  has no epoxy group, (b) an organosiloxane oligomer having SiO bonds, a specified wt. average mol.wt., and specific groups, (c) a polymer containing silyl groups having silicon atoms bonded to hydrolyzable groups and/or hydroxy groups, (d) a photocatalyst, and (e) an organic solvent having a surface tension at 20 deg.C of 260  $\mu N/cm$  or lower. A production method for the composition is also provided.

---

Data supplied from the esp@cenet database - Patent Abstracts of Japan